

NO KNOTS

TIGHT-ROPE™

TWISTER

Line & Rope Tensioning Rod

Made from commercial grade durable Nylon



- Trailers & Motoring
- Pick-Ups
- Fishing & Boating
- Yachting
- Camping
- Gardening
- Carpentry
- D-I-Y Projects
- Sports
- Laundry Lines
- Commercial Applications




**NO
MORE
KNOTS**

TIGHT ROPES - NO KNOTS!

TIGHTENING TWO ENDS OF A ROPE



Depress the rope-grip flippers, and pass ends of the rope through the holes from the same side, as shown in the photo.



Pull both ends of the rope through the TIGHT-ROPE TWISTER until the rope is taut.



Turn the TIGHT-ROPE TWISTER, clockwise to tighten the rope. NOTE: three turns should be the maximum required.



When rope is tight, hook the end of the TIGHT-ROPE TWISTER under the rope. This will lock the TIGHT-ROPE TWISTER in position.

USE YOUR IMAGINATION:

Anywhere that you need to tie a rope and keep it tight, TIGHT-ROPE TWISTER will do the job. This easy to use, safe to handle tool will always keep your ropes tight. If you have a novel way to use a TIGHT-ROPE TWISTER, let us know and we will tell others.

HANDY TIP:


For best results from the TIGHT-ROPE TWISTER always use quality, solid diameter rope.



TIGHTENING A SINGLE ROPE FIXED AT BOTH ENDS



For tightening a rope that is already fixed at both ends, position the TIGHT-ROPE TWISTER on the rope, as shown in the photo.



Loop the rope around the TIGHT-ROPE TWISTER. Turn the TIGHT-ROPE TWISTER, clockwise to tighten the rope. NOTE: three turns should be the maximum required.



Hook the end of the TIGHT-ROPE TWISTER under the rope. This will lock the TIGHT-ROPE TWISTER into position.

TIGHTENING A ROPE FIXED AT ONE END



Depress the rope-grip flipper closest to the hook. Pass the end of the rope through the TIGHT-ROPE TWISTER, and pull until a minimum of 6" (15cm) has gone through or until the rope is taut.



Loop the TIGHT-ROPE TWISTER around the fixed rope, as shown in the photo.



Turn the TIGHT-ROPE TWISTER clockwise to tighten the rope. Then, hook the end of the TIGHT-ROPE TWISTER under the rope. This will lock the TIGHT-ROPE TWISTER into position.

CAUTION: Do not use for towing. Do not use with elasticised ropes. Load limit 225lbs. / 100kg. Observe manufacturer's rope tension limits. Avoid use with frayed or deteriorating ropes.

FOR USE WITH: 3/16" (4mm), 1/4" (6mm), 5/16" (8mm) ropes.

Please read instructions carefully as damage or injury may result from improper use. The manufacturer shall not be liable for any damage or injury resulting from use not in accordance with the instructions.

TIGHT-ROPE™
TWISTER
Line & Rope Tensioning Rod

Patent No. PCT/AU2004/001212
International Patents Pending.

Better Lifestyle Products, LLC
PO Box 4257
Wayne, NJ 07474

Toll-Free: 800-923-2792
Tel: 973-696-2686 Fax: 973-696-2686
E-mail: sales@betterlifestyleproducts.com
URL: www.betterlifestyleproducts.com

